# ETSI EN 300 676-2 V1.5.1 (2011-09)



Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation;

Part 2: Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive

#### Reference

#### REN/ERM-JTFEA-007

Keywords aeronautical, AM, DSB, radio, testing, VHF

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<a href="http://portal.etsi.org/tb/status/status.asp">http://portal.etsi.org/tb/status/status.asp</a></a>

If you find errors in the present document, please send your comment to one of the following services: <u>http://portal.etsi.org/chaircor/ETSI\_support.asp</u>

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011. All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup>, **UMTS**<sup>TM</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**<sup>TM</sup> and **LTE**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intelle	ectual Property Rights	5				
Forew	ord	5				
Introd	uction	5				
1	Scope6					
2	-					
2.1	Normative references					
2.2	Informative references					
3	Definitions and abbreviations					
3.1	Definitions and abbreviations					
3.2	Abbreviations					
4	Technical requirements specifications					
4.1	Environmental profile					
4.2	Conformance requirements					
4.2.1 4.2.1.1	Transmitter requirements					
4.2.1.1 4.2.1.2	1 7					
4.2.1.2 4.2.1.3						
4.2.1.3	J					
4.2.1.5	1					
4.2.1.6						
4.2.1.7						
4.2.2	Receiver requirements					
4.2.2.1	•					
4.2.2.2	·					
4.2.2.3	Spurious response rejection	9				
4.2.2.4	$1$ $\mathbf{J}$					
4.2.2.5	e e e e e e e e e e e e e e e e e e e					
4.2.2.6						
4.2.2.7						
4.2.2.8	Cabinet radiation	9				
5	Testing for compliance with technical requirements	9				
5.1	Environmental conditions for testing					
5.2	Interpretation of the measurement results					
5.3	Essential radio test suites					
5.3.1	Transmitter test specifications					
5.3.1.1	1					
5.3.1.2	- · · · · · · · · · · · · · · · · · · ·					
5.3.1.3	J					
5.3.1.4 5.3.1.5	1					
5.3.1.6						
5.3.1.0						
5.3.1.7	Receiver test specifications					
5.3.2.1	L Company of the Comp					
5.3.2.2						
5.3.2.3						
5.3.2.4	$\mathbf{I}$					
5.3.2.5	1 3					
5.3.2.6	e e e e e e e e e e e e e e e e e e e					
5.3.2.7	· · · · · · · · · · · · · · · · · · ·					
5.3.2.8	Cabinet radiation	.11				

Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	12
Annex B (informative):	The EN title in the official languages	15
Annex C (informative):	Bibliography	16
History		17

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Foreword**

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) [i.4] laying down a procedure for the provision of information in the field of technical standards and regulations.

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.1].

See article 5.1 of Directive 1999/5/EC [i.1] for information on presumption of conformity and Harmonised Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.1] are summarised in annex A.

The present document is part 2 of a multi-part deliverable covering the Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation; as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates			
Date of adoption of this EN:	4 August 2011		
Date of latest announcement of this EN (doa):	30 November 2011		
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2012		
Date of withdrawal of any conflicting National Standard (dow):	31 May 2013		

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.3].

## 1 Scope

The present document applies to DSB AM ground base stations, with channel separations of 8,33 kHz or 25 kHz intended for analogue speech intended for ACARS data communication. The scope of the present document is limited to ground based stations, ground mobile and hand held radios for ground use. These radio equipment types are capable of operating in all or any part of the Aeronautical frequency band- between 118 MHz and 136,975 MHz.

The present document is intended to cover the provisions of Directive 1999/5/EC (R&TTE Directive) [i.1], article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.1] as well as essential requirements under the SES Interoperability Regulation 552/2004 [i.2] and related implementing rules may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <a href="http://www.newapproach.org">http://www.newapproach.org</a>.

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <a href="http://docbox.etsi.org/Reference">http://docbox.etsi.org/Reference</a>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

#### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 676-1 (V1.5.2): "Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation; Part 1: Technical characteristics and methods of measurement".
- [2] ETSI EN 300 113-1 (V1.6.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- [3] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

#### 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity; amended by Regulation (EC) No 1882/2003 of the European Parliament and of the Council of 29/09/2003.

[i.2] Regulation (EC) No 552/2004 of the European Parliament and of the Council of 10 March 2004 on the interoperability of the European Air Traffic Management network (interoperability Regulation), OJ L 96, 31.03.2004, p. 26 as amended by Regulation (EC) No 1070/2009, OJ L 300, 14.11.2009, p. 34.

[i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive"; amended by Regulation (EC) No 1070/2009 of the European Parliament and of the Council of 21/10/2009. Official Journal L 300/34, 14/11/2009.

[i.4] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

### 3 Definitions and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.1] and the following apply:

**aeronautical mobile service:** mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

conducted measurements: measurements which are made using a direct RF connection to the equipment under test

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**ground base station:** aeronautical station equipment, in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location

hand held: radio equipment with integral batteries, designed to be hand portable and operated hand held

**integral antenna equipment:** radio communications equipment with an antenna integrated into the equipment without the use of an external connector and considered to be part of the equipment

NOTE: An integral antenna may be internal or external to the equipment. In equipment of this type, a 50  $\Omega$  RF connection point should be provided for test purposes. A connection point for an AF modulating input and for AF output measurements should also be provided.

**mobile station:** radio equipment designed for permanent or temporary vehicle installation and operation, including provision for vehicle DC power supply, and connections for external antenna, PTT key, microphone, speaker and/or headphone

**non-integral antenna equipment:** radio communications equipment with a connector intended for connection to an antenna

portable station: radio equipment with integral battery for independent hand-carried use

NOTE: Provisions may be made for connections of an external antenna, PTT key, microphone, headphone and charger, but principally to be operated as a self contained unit.

radiated measurements: measurements which involve the measurement of a radiated field

#### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACARS Aircraft Communications Addressing and Reporting System

AF Audio Frequency
AM Amplitude Modulation

DC Direct Current (feeding, signalling)

DSB Double Side Band

ICAO International Civil Aviation Organization

IF Intermediate Frequency

PTT Press To Talk

R&TTE Radio and Telecommunications Terminal Equipment

RF Radio Frequency SES Single European Sky

## 4 Technical requirements specifications

## 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

## 4.2 Conformance requirements

#### 4.2.1 Transmitter requirements

#### 4.2.1.1 Frequency error

The frequency error as defined in clause 7.2 of EN 300 676-1 [1] shall not exceed the values shown in table 1 of EN 300 676-1 [1].

#### 4.2.1.2 Carrier power (conducted)

The carrier power as defined in clause 7.3.1 of EN 300 676-1 [1] shall conform to the requirements in clause 7.3.3 of EN 300 676-1 [1].

#### 4.2.1.3 Adjacent channel power

Adjacent channel power as defined in clause 7.5.1 of EN 300 676-1 [1] shall conform to the requirements in clause 7.5.3 of EN 300 676-1 [1].

#### 4.2.1.4 Conducted spurious emissions

Conducted spurious emissions as defined in clause 7.7.1 of EN 300 676-1 [1] shall conform to the limits in clause 7.7.3, table 3 of EN 300 676-1 [1].

#### 4.2.1.5 Intermodulation attenuation (Applicable to Base stations only)

Intermodulation attenuation as defined in clause 7.8.1 of EN 300 676-1 [1] shall conform to the limits in clause 7.8.3 of EN 300 676-1 [1].

#### 4.2.1.6 Keying transient frequency behaviour (Applicable to base stations only)

Keying transient frequency behaviour as defined in clause 7.10.1 of EN 300 676-1 [1] shall conform to the limits in clause 7.10.3 of EN 300 676-1 [1].

#### 4.2.1.7 Cabinet radiation

The transmitter shall conform to clause 7.12 of EN 300 676-1 [1].

#### 4.2.2 Receiver requirements

NOTE:

These aspects and parameters are considered essential to ensure immediate and successful ground to air communication. Inadequate performance in any of these aspects may lead to retransmission with consequential inefficient use of the spectrum.

#### 4.2.2.1 Sensitivity

Sensitivity as defined in clause 8.1.1 of EN 300 676-1 [1] shall conform to the limits in clause 8.1.3 of EN 300 676-1 [1].

#### 4.2.2.2 Adjacent channel rejection

Adjacent channel rejection as defined in clause 8.6.1 of EN 300 676-1 [1] shall conform to the limits in clause 8.6.3 of EN 300 676-1 [1].

#### 4.2.2.3 Spurious response rejection

Spurious response rejection as defined in clause 8.7.1 of EN 300 676-1 [1] shall conform to the limits in clause 8.7.5 of EN 300 676-1 [1].

#### 4.2.2.4 Intermodulation response rejection

Intermodulation response rejection as defined in clause 8.8.1 of EN 300 676-1 [1] shall conform to the limits in clause 8.8.3 of EN 300 676-1 [1].

#### 4.2.2.5 Blocking or desensitisation

Blocking or desensitisation as defined in clause 8.9.1 of EN 300 676-1 [1] shall conform to the limits in clause 8.9.3 of EN 300 676-1 [1].

#### 4.2.2.6 Conducted spurious emissions

Conducted spurious emissions as defined in clause 8.10.1 of EN 300 676-1 [1] shall conform to the limits in clause 8.10.3 (see table 4) of EN 300 676-1 [1].

#### 4.2.2.7 Cross modulation rejection

Cross modulation rejection as defined in clause 8.12.1 of EN 300 676-1 [1] shall conform to the limits in clause 8.12.3 of EN 300 676-1 [1].

#### 4.2.2.8 Cabinet radiation

The receiver shall conform to clause 8.17 of EN 300 676-1 [1].

## 5 Testing for compliance with technical requirements

## 5.1 Environmental conditions for testing

The test conditions and procedures shall be as defined in clauses 5 and 6 of EN 300 676-1 [1].

## 5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028 [3] and shall correspond to an expansion factor (coverage factor) k = 1,96 or k = 2 (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterising the actual measurement uncertainties are normal (Gaussian)).

Table 1 is based on such expansion factors.

Table 1: Measurement uncertainty: maximum values

Measurement uncertainties	Maximum values
Adjacent channel power	±2,5 dB
Adjacent channel rejection	±4 dB
Blocking and desensitization	±4 dB
Carrier power (normal and extreme test conditions)	±0,75 dB
Conducted spurious emissions:	
below 1 GHz	±3 dB
between 1 GHz and 4 GHz	±6 dB
Conducted spurious radiation:	
below 1 GHz	±3 dB
between 1 GHz and 4 GHz	±6 dB
Cabinet radiation	
Cross modulation rejection	±4 dB
Frequency error	$\pm 1 \times 10^{-9}$
Intermodulation	±3 dB
Intermodulation response rejection	±3 dB
Keying transient frequency behaviour	±3 dB
Receiver dynamic range	±2 dB
Receiver sensitivity	±3 dB
Spurious response rejection	±4 dB
Transient frequency behaviour	±250 Hz

For the test methods according to the present document the uncertainty figures are valid to a confidence level of 95 % calculated according to the methods described in TR 100 028 [3].

#### 5.3 Essential radio test suites

#### 5.3.1 Transmitter test specifications

#### 5.3.1.1 Frequency error

The test procedure specified in clause 7.2.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.1.2 Carrier power (conducted)

The test procedure specified in clause 7.3.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.1.3 Adjacent channel power

The test procedure specified in clause 7.5.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.1.4 Conducted spurious emissions

The test procedure specified in clause 7.7.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.1.5 Intermodulation attenuation

The test procedure specified in clause 7.8.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.1.6 Keying transient frequency behaviour

The test procedure specified in clause 710.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.1.7 Cabinet Radiation

The test specified in clause 7.12 of EN 300 676-1 [1] shall use the test procedure as defined in EN 300 113-1 [2] to measure the cabinet radiation.

#### 5.3.2 Receiver test specifications

#### 5.3.2.1 Sensitivity

The test procedure specified in clause 8.1.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.2.2 Adjacent channel rejection

The test procedure specified in 8 clause.6.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.2.3 Spurious response rejection

The test procedures specified in clause 8.7.3 and clause 8.7.4 of EN 300 676-1 [1] shall be carried out.

#### 5.3.2.4 Intermodulation response rejection

The test procedure specified in clause 8.8.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.2.5 Blocking or desensitisation

The test procedure specified in clause 8.9.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.2.6 Conducted spurious emissions

The test procedure specified in 8.10.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.2.7 Cross modulation rejection

The test procedure specified in clause 8.12.2 of EN 300 676-1 [1] shall be carried out.

#### 5.3.2.8 Cabinet radiation

The test specified in clause 8.17 of EN 300 676-1 [1] shall use the test procedure as defined in EN 300 113-1 [2] to measure the cabinet radiation.

## Annex A (normative): HS Requirements and conformance Test specifications Table (HS-RTT)

The HS Requirements and conformance Test specifications Table (HS-RTT) in table A.1 serves a number of purposes, as follows:

- it provides a statement of all the requirements in words and by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it provides a statement of all the test procedures corresponding to those requirements by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it qualifies each requirement to be either:
  - Unconditional: meaning that the requirement applies in all circumstances, or
  - Conditional: meaning that the requirement is dependent on the manufacturer having chosen to support optional functionality defined within the schedule.
- in the case of Conditional requirements, it associates the requirement with the particular optional service or functionality;
- it qualifies each test procedure to be either:
  - Essential: meaning that it is included with the Essential Radio Test Suite and therefore the requirement shall be demonstrated to be met in accordance with the referenced procedures;
  - Other: meaning that the test procedure is illustrative but other means of demonstrating compliance with the requirement are permitted.

Table A.1: HS Requirements and conformance Test specifications Table (HS-RTT)

	Harmonized Standard EN 300 676-2					
_	The following requirements and test specifications are relevant to the presumption of conformity under the article 3.2 of the R&TTE Directive [i.1]					
Requirement			Requirement Conditionality		Test Specification	
No	Description	Reference:	U/C	Condition	E/O	Reference:
		Clause No				Clause No
1	Frequency error	4.2.1.1	U		E	5.3.1.1
2	Carrier power	4.2.1.2	U		Е	5.3.1.2
3	Adjacent channel power	4.2.1.3	U		E	5.3.1.3
4	Void					
5	Spurious emissions (TX)	4.2.1.4	U		Е	5.3.1.4
6	Intermodulation attenuation	4.2.1.5	С	Base station only	Е	5.3.1.5
7	Keying transient behaviour	4.2.1.6	С	Base station only	Е	5.3.1.6
8	Cabinet Radiation	4.2.1.7	U		Е	5.3.1.7
9	Void					
10	Void					
11	Void					
12	Sensitivity	4.2.2.1	U		Е	5.3.2.1
13	Adjacent channel rejection	4.2.2.2	U		E	5.3.2.2
14	Spurious response rejection	4.2.2.3	U		E	5.3.2.3
15	Intermodulation response rejection	4.2.2.4	U		Е	5.3.2.4
16	Blocking or desensitisation	4.2.2.5	U		Е	5.3.2.5
17	Conducted spurious emissions	4.2.2.6	U		Е	5.3.2.6
18	Void					
19	Cross modulation rejection	4.2.2.7	U		Е	5.3.2.7
20	Cabinet Radiation	4.2.2.8	U		Е	5.3.2.8

#### **Key to columns:**

#### **Requirement:**

**No** A unique identifier for one row of the table which may be used to identify a requirement or

its test specification.

**Description** A textual reference to the requirement.

Clause Number Identification of clause(s) defining the requirement in the present document unless another

document is referenced explicitly.

#### **Requirement Conditionality:**

U/C Indicates whether the requirement is to be *unconditionally* applicable (U) or is *conditional* 

upon the manufacturers claimed functionality of the equipment (C).

**Condition** Explains the conditions when the requirement shall or shall not be applicable for a technical

requirement which is classified "conditional".

#### **Test Specification:**

E/O

Indicates whether the test specification forms part of the Essential Radio Test Suite (E) or whether it is one of the Other Test Suite (O).

NOTE:

All tests whether "E" or "O" are relevant to the requirements. Rows designated "E" collectively make up the Essential Radio Test Suite; those designated "O" make up the Other Test Suite; for those designated "X" there is no test specified corresponding to the requirement. The completion of all tests classified "E" as specified with satisfactory outcomes is a necessary condition for a presumption of conformity. Compliance with requirements associated with tests classified "O" or "X" is a necessary condition for presumption of conformity, although conformance with the requirement may be claimed by an equivalent test or by manufacturer's assertion supported by appropriate entries in the technical construction file.

**Clause Number** 

Identification of clause(s) defining the test specification in the present document unless another document is referenced explicitly. Where no test is specified (that is, where the previous field is "X") this field remains blank.

# Annex B (informative): The EN title in the official languages

The enlargement of the European Union (EU) resulted in a requirement from the EU for a larger number of languages for the translation of the titles of Harmonized Standards and mandated ENs that are to be listed in the Official Journal to support the implementation of this legislation.

For this reason the title translation concerning the present document can be consulted via the <u>e-approval</u> application.

# Annex C (informative): Bibliography

Commission Regulation (EC) No 1265/2007 of 26 October 2007 laying down requirements on air-ground voice channel spacing for the single European sky (Text with EEA relevance), OJEU L283, 27.10.2007, p. 25-36.

ITU-T Recommendation O.41: "Psophometer for use on telephone-type circuits".

ISO 7637 (parts 1 and 2): "Road vehicles - Electrical disturbances from conduction and coupling".

ICAO annex 10 volume V (July 2001, including amendments up to amendment 83): "Aeronautical Radio Frequency Spectrum Utilization".

Directive 2004/108/EC of the European Parliament and of the Council of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 89/336/EEC (EMC Directive).

Directive 2006/95/EC of the European Parliament and of the Council of 12 December 2006 on the harmonisation of the laws of Member States relating to electrical equipment designed for use within certain voltage limits (LV Directive).

# History

Document history				
V1.4.1	April 2010	Publication		
V1.5.0	April 2011	One-step Approval Procedure OAP 20110804: 2011-04-06 to 2011-08-04		
V1.5.1	September 2011	Publication		