



**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
VHF radiotelephone equipment for general communications
and associated equipment for Class "D"
Digital Selective Calling (DSC);
Part 3: Harmonized EN covering the essential requirements
of article 3.3(e) of the R&TTE Directive**

ReferenceREN/ERM-TG26-101-3

KeywordsDSC, maritime, radio, traffic, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references	8
3 Definitions and abbreviations.....	9
3.1 Definitions	9
3.2 Abbreviations	9
4 Technical requirements specifications	9
4.1 Environmental profile.....	9
4.2 General, operational and technical requirements.....	10
4.2.1 General and operational requirements	10
4.2.1.1 Requirements	10
4.2.1.2 Conformance.....	10
4.2.2 Technical requirements	10
4.2.2.1 Requirements	10
4.2.2.2 Conformance.....	10
4.3 Environmental requirements	10
4.3.1 Vibration test	10
4.3.1.1 Definition	10
4.3.1.2 Requirement	10
4.3.1.3 Conformance.....	10
4.3.2 Temperature tests	10
4.3.2.1 Definition	10
4.3.2.2 Dry heat.....	11
4.3.2.2.1 Definition.....	11
4.3.2.2.2 Requirement	11
4.3.2.2.3 Conformance	11
4.3.2.3 Damp heat	11
4.3.2.3.1 Definition.....	11
4.3.2.3.2 Requirement	11
4.3.2.3.3 Conformance	11
4.3.2.4 Low temperature	11
4.3.2.4.1 Definition.....	11
4.3.2.4.2 Requirement	11
4.3.2.4.3 Conformance	11
4.4 Conformance requirements	11
4.4.1 Sensitivity of the modulator, including microphone.....	11
4.4.1.1 Definition	11
4.4.1.2 Limit.....	11
4.4.1.3 Conformance.....	12
4.4.2 Audio frequency response	12
4.4.2.1 Definition	12
4.4.2.2 Limit.....	12
4.4.2.3 Conformance.....	12
4.4.3 Audio frequency harmonic distortion of the emission	12
4.4.3.1 Definition	12
4.4.3.2 Limit.....	12
4.4.3.3 Conformance.....	12
4.4.4 Residual modulation of the transmitter	12
4.4.4.1 Definition	12

4.4.4.2	Limit.....	12
4.4.4.3	Conformance.....	12
4.4.5	Frequency error (demodulated DSC signal)	12
4.4.5.1	Definition	12
4.4.5.2	Limit.....	12
4.4.5.3	Conformance.....	13
4.4.6	Modulation index for DSC	13
4.4.6.1	Definition	13
4.4.6.2	Limit.....	13
4.4.6.3	Conformance.....	13
4.4.7	Modulation rate for DSC	13
4.4.7.1	Definition	13
4.4.7.2	Limit.....	13
4.4.7.3	Conformance.....	13
4.4.8	Void	13
4.4.9	Harmonic distortion and rated audio-frequency output power	13
4.4.9.1	Definition	13
4.4.9.2	Limit.....	13
4.4.9.3	Conformance.....	13
4.4.10	Receiver audio frequency response	13
4.4.10.1	Definition	13
4.4.10.2	Limit.....	14
4.4.10.3	Conformance.....	14
4.4.11	Receiver residual noise level	14
4.4.11.1	Definition	14
4.4.11.2	Limit.....	14
4.4.11.3	Conformance.....	14
4.4.12	Squelch operation	14
4.4.12.1	Definition	14
4.4.12.2	Limit.....	14
4.4.12.3	Conformance.....	14
4.4.13	Squelch hysteresis.....	14
4.4.13.1	Definition	14
4.4.13.2	Limit.....	14
4.4.13.3	Conformance.....	14
4.4.14	Dynamic range.....	14
4.4.14.1	Definition	14
4.4.14.2	Limit.....	15
4.4.14.3	Conformance.....	15
4.5	DSC Signalling.....	15
4.5.1	Display	15
4.5.2	Watchkeeping receiver	15
4.5.3	Individual DSC calls.....	15
4.5.4	All ships calls.....	15
4.5.5	DSC call functionality	15
4.5.6	DSC message composition	15
4.5.7	Prioritized wait.....	15
4.5.8	Alarms	15
4.5.9	Standby	15
4.5.10	Sending distress automated requirements	15
4.5.11	Display	15
4.5.12	Distress button sub procedure	16
4.5.13	Transmission of the alert attempt.....	16
4.5.14	Updating position.....	16
4.5.15	Handling received DSC messages	16
4.5.16	Alarms	16
4.5.17	Determining subsequent communications	16
4.5.18	Automated tuning	16
4.5.19	Cancelling the distress alert	16
4.5.20	Acknowledgements.....	16
4.5.21	Termination.....	16
4.5.22	Warnings.....	16

4.5.23	Tasks – receiving distress	16
4.5.24	Display – receiving distress	17
4.5.25	Handling received DSC messages – receiving distress.....	17
4.5.26	Alarms – receiving distress.....	17
4.5.27	Determining subsequent communications – receiving distress.....	17
4.5.28	Automated tuning – receiving distress.....	17
4.5.29	Acknowledgements – receiving distress	17
4.5.30	Termination – receiving distress	17
4.5.31	Warnings – receiving distress	17
4.5.32	Tasks – sending non distress.....	17
4.5.33	Display – sending non distress.....	17
4.5.34	Handling received DSC messages – sending non distress	17
4.5.35	Alarms – sending non distress	17
4.5.36	Automated tuning – sending non distress	17
4.5.37	Delayed acknowledgements – sending non distress	18
4.5.38	Termination – sending non distress	18
4.5.39	Warnings – sending non distress.....	18
4.5.40	Tasks – receiving non distress	18
4.5.41	Display – receiving non distress	18
4.5.42	Handling received DSC messages – receiving non distress.....	18
4.5.43	Alarms – receiving non distress.....	18
4.5.44	Automated tuning – receiving non distress.....	18
4.5.45	Acknowledgements – receiving non distress	18
4.5.46	Termination – receiving non distress	18
4.5.47	Warnings – receiving non distress	18
4.5.48	Communication automated procedure	18
4.5.49	Tasks – communication	18
4.5.50	Display – communication	19
4.5.51	Handling received DSC messages – communication.....	19
4.5.52	Tuning of the receiver and transmitter – communication	19
4.5.53	Termination – communication.....	19
4.5.54	Tasks of handling incoming calls while engaged	19
4.5.55	Termination of automated procedures	19
4.5.56	Actions after termination of an automated procedure.....	19
4.5.57	Putting automated procedures on hold.....	19
4.5.58	Controlling non-terminated automated procedures on hold.....	19
5	Testing for compliance with technical requirements.....	19
5.1	Test conditions, power supply and ambient temperatures	19
5.2	Interpretation of the measurement results	19
5.3	Essential radio test suites.....	20
5.3.1	Environmental tests.....	20
5.3.1.1	Introduction.....	20
5.3.1.2	Procedure	20
5.3.1.3	Performance check.....	20
5.3.1.4	Vibration test.....	20
5.3.1.4.1	Definition.....	20
5.3.1.4.2	Limit	20
5.3.1.4.3	Conformance	20
5.3.1.5	Temperature tests	21
5.3.1.5.1	Dry heat	21
5.3.1.5.2	Damp heat.....	21
5.3.1.5.3	Low temperature.....	21
5.3.2	Conformance tests	21
5.3.2.1	Sensitivity of the modulator, including microphone	21
5.3.2.2	Audio frequency response.....	21
5.3.2.3	Audio frequency harmonic distortion of the emission	22
5.3.2.4	Residual modulation of the transmitter	22
5.3.2.5	Frequency error (demodulated DSC signal).....	22
5.3.2.6	Modulation index for DSC.....	22
5.3.2.7	Modulation rate for DSC.....	22
5.4	Other test suites - Radio	22

5.4.1	General.....	22
5.4.2	Harmonic distortion and rated audio-frequency output power	22
5.4.3	Receiver audio frequency response	22
5.4.4	Receiver residual noise level	22
5.4.5	Squelch operation	22
5.4.6	Squelch hysteresis.....	22
5.4.7	Dynamic range.....	23
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	24
History		28

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to mandate M/357 from the European Commission issued under Directive 98/34/EC [i.4] as amended by Directive 98/48/EC [i.7].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.1].

See article 5.1 of Directive 1999/5/EC [i.1] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.1] are summarised in annex A.

The present document is part 3 of a multi-part deliverable covering the VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC), as identified below:

- Part 1: "Technical characteristics and methods of measurement";
- Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 3: "Harmonized EN covering the essential requirements of article 3.3(e) of the R&TTE Directive".**

National transposition dates	
Date of adoption of this EN:	23 September 2013
Date of latest announcement of this EN (doa):	31 December 2013
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2014
Date of withdrawal of any conflicting National Standard (dow):	30 June 2015

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.6].

1 Scope

The present document covers the minimum requirements for general communication for shipborne fixed installations using a VHF radiotelephone operating in certain frequency bands allocated to the maritime mobile service using 25 kHz or 12,5 kHz and 12,5 kHz channels with associated equipment for DSC - class D.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.1] (R&TTE Directive) article 3.3(e), which states that: "... *radio equipment within the scope of the present document shall be so constructed that it supports certain features ensuring access to emergency services*".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.1] will apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 025-1 (V1.5.2) (05-2013): "Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC); Part 1: Technical characteristics and methods of measurement".
- [2] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [3] ETSI EN 300 338-3 (V1.1.1) (02-2010): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 3: Class D DSC".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] Void.

- [i.3] EC Decision 2004/71/EC of 4 September 2003 on essential requirements relating to marine radio communication equipment which is intended to be used on non-SOLAS vessels and to participate in the Global Maritime Distress and Safety System (GMDSS).
- [i.4] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.5] Void.
- [i.6] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.7] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.1] and the following apply:

class D: class D equipment is intended to provide minimum facilities for VHF DSC distress, urgency and safety as well as routine calling and reception, not necessarily in full accordance with IMO GMDSS carriage requirements for VHF installations

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

G2B: phase-modulation with digital information, with a sub-carrier for DSC operation

G3E: phase-modulation (Frequency modulation with a pre-emphasis of 6 dB/octave) for speech

modulation index: ratio between the frequency deviation and the frequency of the modulation signal

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

DSC	Digital Selective Calling
IMO	International Maritime Organization
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
SINAD	Signal, Noise And Distortion
SOLAS	Safety Of Life And Sea
VHF	Very High Frequency

4 Technical requirements specifications

4.1 Environmental profile

Tests defined in the present document shall be carried out at representative points within the boundary limits of the declared operational environmental profile which, as a minimum, shall be that specified in the test conditions contained in the present document.

As technical performance varies subject to environmental conditions, tests shall be carried out under a sufficient variety of environmental conditions as specified in the present document to give confidence of compliance for the affected technical requirements. These environmental conditions represent those required by article 2 of EC decision 2004/71/EC [i.3] (which shall also be within the boundary limits of the declared operational environmental profile).

4.2 General, operational and technical requirements

4.2.1 General and operational requirements

4.2.1.1 Requirements

The general and operational requirements are defined in EN 301 025-1 [1], clause 4.

4.2.1.2 Conformance

The manufacturer shall declare that compliance to these requirements is achieved and shall provide relevant documentation.

4.2.2 Technical requirements

4.2.2.1 Requirements

The technical requirements are defined in EN 301 025-1 [1], clause 5.

4.2.2.2 Conformance

The manufacturer shall declare that compliance to these requirements is achieved and shall provide relevant documentation.

4.3 Environmental requirements

4.3.1 Vibration test

4.3.1.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.4.1.

4.3.1.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [1], clause 7.3.

There shall be no harmful deterioration of the equipment visible.

4.3.1.3 Conformance

Relevant environment tests as defined in clause 5.3.1.4 shall be carried out.

4.3.2 Temperature tests

4.3.2.1 Definition

This series of tests is defined in EN 301 025-1 [1], clause 7.5.1.

4.3.2.2 Dry heat

4.3.2.2.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.5.2.1.

4.3.2.2.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [1], clause 7.3.

4.3.2.2.3 Conformance

Relevant environment tests as defined in clause 5.3.1.5.1 shall be carried out.

4.3.2.3 Damp heat

4.3.2.3.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.5.3.1.

4.3.2.3.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [1], clause 7.3.

4.3.2.3.3 Conformance

Relevant environment tests as defined in clause 5.3.1.5.2 shall be carried out.

4.3.2.4 Low temperature

4.3.2.4.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.5.4.1.

4.3.2.4.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [1], clause 7.3.

4.3.2.4.3 Conformance

Relevant environment tests as defined in clause 5.3.1.3 shall be carried out.

4.4 Conformance requirements

4.4.1 Sensitivity of the modulator, including microphone

4.4.1.1 Definition

This test is defined in EN 301 025-1 [1], clause 8.4.1.

4.4.1.2 Limit

The frequency deviation shall be as stated in EN 301 025-1 [1], clause 8.4.3.

4.4.1.3 Conformance

Conformance tests as defined in clause 5.3.2.1 shall be carried out.

4.4.2 Audio frequency response

4.4.2.1 Definition

This test is defined in EN 301 025-1 [1], clause 8.5.1.

4.4.2.2 Limit

The audio frequency response shall lie within the limits shown in EN 301 025-1 [1], clause 8.5.3, figure 2.

4.4.2.3 Conformance

Conformance tests as defined in clause 5.3.2.2 shall be carried out.

4.4.3 Audio frequency harmonic distortion of the emission

4.4.3.1 Definition

This test is defined in EN 301 025-1 [1], clause 8.6.1.

4.4.3.2 Limit

The harmonic distortion limit shall be as stated in EN 301 025-1 [1], clause 8.6.3.

4.4.3.3 Conformance

Conformance tests as defined in clause 5.3.2.3 shall be carried out.

4.4.4 Residual modulation of the transmitter

4.4.4.1 Definition

This test is defined in EN 301 025-1 [1], clause 8.11.1.

4.4.4.2 Limit

The residual modulation shall not exceed the limit stated in EN 301 025-1 [1], clause 8.11.3.

4.4.4.3 Conformance

Conformance tests as defined in clause 5.3.2.4 shall be carried out.

4.4.5 Frequency error (demodulated DSC signal)

4.4.5.1 Definition

This test is defined in EN 301 025-1 [1], clause 8.12.1.

4.4.5.2 Limit

The frequency error shall not exceed the limit stated in EN 301 025-1 [1], clause 8.12.3.

4.4.5.3 Conformance

Conformance tests as defined in clause 5.3.2.5 shall be carried out.

4.4.6 Modulation index for DSC

4.4.6.1 Definition

This test is defined in EN 301 025-1 [1], clause 8.13.1.

4.4.6.2 Limit

The modulation index shall not exceed the limit stated in EN 301 025-1 [1], clause 8.13.3.

4.4.6.3 Conformance

Conformance tests as defined in clause 5.3.2.6 shall be carried out.

4.4.7 Modulation rate for DSC

4.4.7.1 Definition

This test is defined in EN 301 025-1 [1], clause 8.14.1.

4.4.7.2 Limit

The frequency shall not exceed the limit stated in EN 301 025-1 [1], clause 8.13.3.

4.4.7.3 Conformance

Conformance tests as defined in clause 5.3.2.7 shall be carried out.

4.4.8 Void

4.4.9 Harmonic distortion and rated audio-frequency output power

4.4.9.1 Definition

This test is defined in EN 301 025-1 [1], clause 9.1.1.

4.4.9.2 Limit

The rated audio-frequency output power shall comply with the limits stated in EN 301 025-1 [1], clause 9.1.3.

4.4.9.3 Conformance

Conformance tests as defined in clause 5.4.2 may be carried out.

4.4.10 Receiver audio frequency response

4.4.10.1 Definition

This test is defined in EN 301 025-1 [1], clause 9.2.1.

4.4.10.2 Limit

The audio frequency response shall lie within the limits shown in EN 301 025-1 [1], clause 9.2.3, figure 5.

4.4.10.3 Conformance

Conformance tests as defined in clause 5.4.3 may be carried out.

4.4.11 Receiver residual noise level

4.4.11.1 Definition

This test is defined in EN 301 025-1 [1], clause 9.11.1.

4.4.11.2 Limit

The receiver residual noise level shall not exceed the limit stated in EN 301 025-1 [1], clause 9.11.3.

4.4.11.3 Conformance

Conformance tests as defined in clause 5.4.4 may be carried out.

4.4.12 Squelch operation

4.4.12.1 Definition

This test is defined in EN 301 025-1 [1], clause 9.12.1.

4.4.12.2 Limit

The squelch operation shall comply with the limits stated in EN 301 025-1 [1], clause 9.12.3.

4.4.12.3 Conformance

Conformance tests as defined in clause 5.4.5 may be carried out.

4.4.13 Squelch hysteresis

4.4.13.1 Definition

This test is defined in EN 301 025-1 [1], clause 9.13.1.

4.4.13.2 Limit

The squelch hysteresis shall comply with the limits stated in EN 301 025-1 [1], clause 9.13.3.

4.4.13.3 Conformance

Conformance tests as defined in clause 5.4.6 may be carried out.

4.4.14 Dynamic range

4.4.14.1 Definition

This test is defined in EN 301 025-1 [1], clause 10.6.1.

4.4.14.2 Limit

The bit error ratio shall not exceed the limit stated in EN 301 025-1 [1], clause 10.6.3.

4.4.14.3 Conformance

Conformance tests as defined in clause 5.4.7 may be carried out.

4.5 DSC Signalling

4.5.1 Display

The radio shall comply with the display requirements given in clause 4.1 of EN 300 338-3 [3].

4.5.2 Watchkeeping receiver

The radio shall comply with the watchkeeping receiver requirements given in clause 5.1.1 of EN 300 338-3 [3].

4.5.3 Individual DSC calls

The radio shall comply with the individual calls requirements given in clause 5.2.2 of EN 300 338-3 [3].

4.5.4 All ships calls

The radio shall comply with the all ships calls requirements given in clause 5.2.3 of EN 300 338-3 [3].

4.5.5 DSC call functionality

The radio shall comply with the DSC call functionality requirements given in clause 5.2.4 of EN 300 338-3 [3].

4.5.6 DSC message composition

The radio shall comply with the DSC message composition requirements given in clause 6.2.1 of EN 300 338-3 [3].

4.5.7 Prioritized wait

The radio shall comply with the prioritized wait requirements given in clause 6.2.2 of EN 300 338-3 [3].

4.5.8 Alarms

The radio shall comply with the alarms requirements given in clause 6.2.3 of EN 300 338-3 [3].

4.5.9 Standby

The radio shall comply with the standby requirements given in clause 6.3 of EN 300 338-3 [3].

4.5.10 Sending distress automated requirements

The radio shall comply with the sending distress automated requirements given in clause 6.4.2 of EN 300 338-3 [3] except that the "Sending distress" procedure shown in figure 1 of [3] should be treated as an example and not as a mandatory requirement.

4.5.11 Display

The radio shall comply with the display requirements given in clause 6.4.3 of EN 300 338-3 [3].

4.5.12 Distress button sub procedure

The radio shall comply with the dedicated distress button sub procedure requirements given in clause 6.4.4 of EN 300 338-3 [3] except for the following requirement (bullet c) of [3]): "*when releasing the button the radio shall return to its previous state*", which shall be optional.

4.5.13 Transmission of the alert attempt

The radio shall comply with the transmission of the alert attempt requirements given in clause 6.4.5 of EN 300 338-3 [3].

4.5.14 Updating position

The radio shall comply with the updating position requirements given in clause 6.4.6 of EN 300 338-3 [3].

4.5.15 Handling received DSC messages

The radio shall comply with the requirements for handling received DSC messages given in clause 6.4.7 of EN 300 338-3 [3].

4.5.16 Alarms

The radio shall comply with the alarms requirements given in clause 6.4.8 of EN 300 338-3 [3].

4.5.17 Determining subsequent communications

The radio shall comply with the requirements given in clause 6.4.9 of EN 300 338-3 [3].

4.5.18 Automated tuning

The radio shall comply with the requirements given in clause 6.4.10 of EN 300 338-3 [3].

4.5.19 Cancelling the distress alert

The radio shall comply with the distress cancel requirements given in clause 6.4.11 of EN 300 338-3 [3].

4.5.20 Acknowledgements

The radio shall comply with the acknowledgements requirements given in clause 6.4.12 of EN 300 338-3 [3].

4.5.21 Termination

The radio shall comply with the termination requirements given in clause 6.4.13 of EN 300 338-3 [3].

4.5.22 Warnings

The radio shall comply with the warnings requirements given in clause 6.4.14 of EN 300 338-3 [3].

4.5.23 Tasks – receiving distress

The radio shall comply with the task requirements given in clause 6.5.2 of EN 300 338-3 [3] except that the "received distress automated" procedure shown in figure 2 of [3] should be treated as an example and not as a mandatory requirement.

4.5.24 Display – receiving distress

The radio shall comply with the display requirements given in clause 6.5.3 of EN 300 338-3 [3].

4.5.25 Handling received DSC messages – receiving distress

The radio shall comply with the requirements for handling received DSC messages given in clause 6.5.4 of EN 300 338-3 [3].

4.5.26 Alarms – receiving distress

The radio shall comply with the alarms requirements given in clause 6.5.5 of EN 300 338-3 [3].

4.5.27 Determining subsequent communications – receiving distress

The radio shall comply with the requirements given in clause 6.5.6 of EN 300 338-3 [3].

4.5.28 Automated tuning – receiving distress

The radio shall comply with the requirements given in clause 6.5.7 of EN 300 338-3 [3].

4.5.29 Acknowledgements – receiving distress

The radio shall comply with the acknowledgements requirements given in clause 6.5.8 of EN 300 338-3 [3].

4.5.30 Termination – receiving distress

The radio shall comply with the termination requirements given in clause 6.5.9 of EN 300 338-3 [3].

4.5.31 Warnings – receiving distress

The radio shall comply with the warnings requirements given in clause 6.5.10 of EN 300 338-3 [3].

4.5.32 Tasks – sending non distress

The radio shall comply with the task requirements given in clause 6.6.2 of EN 300 338-3 [3] except that the "Sending non distress automated" procedure shown in figure 3 of [3] should be treated as an example and not as a mandatory requirement.

4.5.33 Display – sending non distress

The radio shall comply with the display requirements given in clause 6.6.3 of EN 300 338-3 [3].

4.5.34 Handling received DSC messages – sending non distress

The radio shall comply with the requirements for handling received DSC messages given in clause 6.6.4 of EN 300 338-3 [3].

4.5.35 Alarms – sending non distress

The radio shall comply with the alarms requirements given in clause 6.6.5 of EN 300 338-3 [3].

4.5.36 Automated tuning – sending non distress

The radio shall comply with the requirements given in clause 6.6.6 of EN 300 338-3 [3].

4.5.37 Delayed acknowledgements – sending non distress

The radio shall comply with the acknowledgements requirements given in clause 6.6.7 of EN 300 338-3 [3].

4.5.38 Termination – sending non distress

The radio shall comply with the termination requirements given in clause 6.6.8 of EN 300 338-3 [3].

4.5.39 Warnings – sending non distress

The radio shall comply with the warnings requirements given in clause 6.6.9 of EN 300 338-3 [3].

4.5.40 Tasks – receiving non distress

The radio shall comply with the task requirements given in clause 6.7.2 of EN 300 338-3 [3] except that the "Receiving non distress" procedure shown in figure 4 of [3] should be treated as an example and not as a mandatory requirement.

4.5.41 Display – receiving non distress

The radio shall comply with the display requirements given in clause 6.7.3 of EN 300 338-3 [3].

4.5.42 Handling received DSC messages – receiving non distress

The radio shall comply with the requirements for handling received DSC messages given in clause 6.7.4 of EN 300 338-3 [3].

4.5.43 Alarms – receiving non distress

The radio shall comply with the alarms requirements given in clause 6.7.5 of EN 300 338-3 [3].

4.5.44 Automated tuning – receiving non distress

The radio shall comply with the requirements given in clause 6.7.6 of EN 300 338-3 [3].

4.5.45 Acknowledgements – receiving non distress

The radio shall comply with the acknowledgements requirements given in clause 6.7.7 of EN 300 338-3 [3].

4.5.46 Termination – receiving non distress

The radio shall comply with the termination requirements given in clause 6.7.8 of EN 300 338-3 [3].

4.5.47 Warnings – receiving non distress

The radio shall comply with the warnings requirements given in clause 6.7.9 of EN 300 338-3 [3].

4.5.48 Communication automated procedure

The radio shall comply with the requirements given in clause 6.8.1 of EN 300 338-3 [3] except that the bullets (i)-(iii) describing which specific events should result in the communication automated procedure shall be optional.

4.5.49 Tasks – communication

The radio shall comply with the task requirements given in clause 6.8.2 of EN 300 338-3 [3].

4.5.50 Display – communication

The radio shall comply with the display requirements given in clause 6.8.3 of EN 300 338-3 [3].

4.5.51 Handling received DSC messages – communication

The radio shall comply with the requirements for handling received DSC messages given in clause 6.8.4 of EN 300 338-3 [3].

4.5.52 Tuning of the receiver and transmitter – communication

The radio shall comply with the requirements given in clause 6.8.5 of EN 300 338-3 [3].

4.5.53 Termination – communication

The procedure shall be able to be terminated either by the user or automatic timeout.

4.5.54 Tasks of handling incoming calls while engaged

The radio shall comply with the task requirements given in clause 6.9.2 of EN 300 338-3 [3], except that clauses 6.9.2.1 and 6.9.2.2 shall be optional.

4.5.55 Termination of automated procedures

The radio shall comply with the requirements given in clause 6.9.2.3 of EN 300 338-3 [3].

4.5.56 Actions after termination of an automated procedure

The radio shall comply with the requirements given in clause 6.9.2.4 of EN 300 338-3 [3] except that bullet (b) need not apply.

4.5.57 Putting automated procedures on hold

The radio may comply with the requirements given in clause 6.9.2.5 of EN 300 338-3 [3].

4.5.58 Controlling non-terminated automated procedures on hold

The radio may comply with the requirements given in clause 6.9.2.6 of EN 300 338-3 [3].

5 Testing for compliance with technical requirements

5.1 Test conditions, power supply and ambient temperatures

The general conditions for measurement as stated in EN 301 025-1 [1], clause 6 shall apply.

5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether an equipment meets the requirements of the present document;

- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [2] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 1 is based on such expansion factors.

Table 1: Maximum measurement uncertainty

Parameter	Maximum uncertainty
Radio Frequency (RF)	$\pm 1 \times 10^{-7}$
RF power/level	$\pm 0,75$ dB
Audio output power	$\pm 0,5$ dB
Amplitude characteristics of receiver limiter	$\pm 1,5$ dB
Sensitivity at 20 dB SINAD	± 3 dB
Two-signal measurement	± 4 dB
Three-signal measurement	± 3 dB

5.3 Essential radio test suites

5.3.1 Environmental tests

5.3.1.1 Introduction

Environmental tests shall be carried out before tests are performed on the same equipment with respect to the other requirements of the present document.

5.3.1.2 Procedure

This test procedure is defined in EN 301 025-1 [1], clause 7.2.

5.3.1.3 Performance check

The "performance check" series of tests are defined in EN 301 025-1 [1], clause 7.3.

5.3.1.4 Vibration test

5.3.1.4.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.4.1.

5.3.1.4.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [1], clause 7.3.

There shall be no harmful deterioration of the equipment visible.

5.3.1.4.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.1.5 Temperature tests

5.3.1.5.1 Dry heat

5.3.1.5.1.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.5.2.1.

5.3.1.5.1.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [1], clause 7.3.

5.3.1.5.1.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.1.5.2 Damp heat

5.3.1.5.2.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.5.3.1.

5.3.1.5.2.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [1], clause 7.3.

5.3.1.5.2.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.1.5.3 Low temperature

5.3.1.5.3.1 Definition

This test is defined in EN 301 025-1 [1], clause 7.5.4.1.

5.3.1.5.3.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [1], clause 7.3.

5.3.1.5.3.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.2 Conformance tests

5.3.2.1 Sensitivity of the modulator, including microphone

The test specified in EN 301 025-1 [1], clause 8.4.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.1.2 in order to prove compliance with the requirement.

5.3.2.2 Audio frequency response

The test specified in EN 301 025-1 [1], clause 8.5.2 shall be carried out.

The results obtained shall be compared to the limits in clause 4.4.2.2 in order to prove compliance with the requirement.

5.3.2.3 Audio frequency harmonic distortion of the emission

The test specified in EN 301 025-1 [1], clause 8.6.2 shall be carried out. The results obtained under each of the stated test conditions shall be compared to the limits in clause 4.4.3.2 in order to prove compliance with the requirement.

5.3.2.4 Residual modulation of the transmitter

The test specified in EN 301 025-1 [1], clause 8.11.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.4.2 in order to prove compliance with the requirement.

5.3.2.5 Frequency error (demodulated DSC signal)

The test specified in EN 301 025-1 [1], clause 8.12.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.5.2 in order to prove compliance with the requirement.

5.3.2.6 Modulation index for DSC

The test specified in EN 301 025-1 [1], clause 8.13.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.6.2 in order to prove compliance with the requirement.

5.3.2.7 Modulation rate for DSC

The test specified in EN 301 025-1 [1], clause 8.14.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.7.2 in order to prove compliance with the requirement.

5.4 Other test suites - Radio

5.4.1 General

The requirements in clauses 4.4.9 to 4.4.15 inclusive have been set on the assumption that the test specifications in clauses 5.4.2 to 5.4.8 will be used to verify the performance of the equipment.

5.4.2 Harmonic distortion and rated audio-frequency output power

The test specified in EN 301 025-1 [1], clause 9.1.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.9.2 in order to prove compliance with the requirement.

5.4.3 Receiver audio frequency response

The test specified in EN 301 025-1 [1], clause 9.2.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.10.2 in order to prove compliance with the requirement.

5.4.4 Receiver residual noise level

The test specified in EN 301 025-1 [1], clause 9.11.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.11.2 in order to prove compliance with the requirement.

5.4.5 Squelch operation

The test specified in EN 301 025-1 [1], clause 9.12.2 shall be carried out. The results obtained in each of the tests shall be compared to the appropriate limits in clause 4.4.12.2 in order to prove compliance with the requirement.

5.4.6 Squelch hysteresis

The test specified in EN 301 025-1 [1], clause 9.13.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.13.2 in order to prove compliance with the requirement.

5.4.7 Dynamic range

The test specified in EN 301 025-1 [1], clause 10.6.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.14.2 in order to prove compliance with the requirement.

Annex A (normative): HS Requirements and conformance Test specifications Table (HS-RTT)

The HS Requirements and conformance Test specifications Table (HS-RTT) in table A.1 serves a number of purposes, as follows:

- it provides a statement of all the requirements in words and by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it provides a statement of all the test procedures corresponding to those requirements by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it qualifies each requirement to be either:
 - Unconditional: meaning that the requirement applies in all circumstances; or
 - Conditional: meaning that the requirement is dependent on the supplier having chosen to support optional functionality defined within the schedule.
- in the case of Conditional requirements, it associates the requirement with the particular optional service or functionality;
- it qualifies each test procedure to be either:
 - Essential: meaning that it is included with the Essential Radio Test Suite and therefore the requirement shall be demonstrated to be met in accordance with the referenced procedures;
 - Other: meaning that the test procedure is illustrative but other means of demonstrating compliance with the requirement are permitted;

Table A.1: HS Requirements and conformance Test specifications Table (HS-RTT)

Harmonized Standard EN 301 025-3 The following requirements and test specifications are relevant to the presumption of conformity under article 3.3(e) of the R&TTE Directive [i.1]						
Requirement			Requirement Conditionality		Test Specification	
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No
1	General and operational requirements	4.2.1	U		X	
2	Technical requirements	4.2.2	U		X	
3	Vibration test	4.3.1	U		E	5.3.1.4
4	Dry heat	4.3.2.2	U		E	5.3.1.5.1
5	Damp heat	4.3.2.3	U		E	5.3.1.5.2
6	Low temperature	4.3.2.4	U		E	5.3.1.5.3
7	Sensitivity of the modulator, including microphone	4.4.1	U		E	5.3.2.1
8	Audio frequency response	4.4.2	U		E	5.3.2.2
9	Audio frequency harmonic distortion of the emission	4.4.3	U		E	5.3.2.3
10	Residual modulation of the transmitter	4.4.4	U		E	5.3.2.4
11	Frequency error (demodulated DSC signal)	4.4.5	U		E	5.3.2.5
12	Modulation index for DSC	4.4.6	U		E	5.3.2.6
13	Modulation rate for DSC	4.4.7	U		E	5.3.2.7
14	Harmonic distortion and rated audio-frequency output power	4.4.9	U		O	5.4.2
15	Receiver audio frequency response	4.4.10	U		O	5.4.3
16	Receiver residual noise level	4.4.11	U		O	5.4.4

Harmonized Standard EN 301 025-3 The following requirements and test specifications are relevant to the presumption of conformity under article 3.3(e) of the R&TTE Directive [i.1]						
Requirement			Requirement Conditionality		Test Specification	
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No
17	Squelch operation	4.4.12	U		O	5.4.5
18	Squelch hysteresis	4.4.13	U		O	5.4.6
19	Dynamic range	4.4.14	U		O	5.4.7
20	Display	4.5.1	U		X	
21	Watchkeeping receiver	4.5.2	U		X	
22	Individual DSC calls	4.5.3	U		X	
23	All ships calls	4.5.4	U		X	
24	DSC call functionality	4.5.5	U		X	
25	DSC message composition	4.5.6	U		X	
26	Prioritized wait	4.5.7	U		X	
27	Alarms	4.5.8	U		X	
28	Standby	4.5.9	U		X	
29	Tasks - sending distress	4.5.10	U		X	
30	Display - sending distress	4.5.11	U		X	
31	Distress button sub-procedure	4.5.12	U		X	
32	Transmission of alert attempt	4.5.13	U		X	
33	Updating position	4.5.14	U		X	
34	Handling received DSC messages – sending distress	4.5.15	U		X	
35	Alarms – sending distress	4.5.16	U		X	
36	Determining subsequent communication – sending distress	4.5.17	U		X	
37	Automated tuning – sending distress	4.5.18	U		X	
38	Cancelling the distress alert	4.5.19	U		X	
39	Acknowledgement – sending distress	4.5.20	U		X	
40	Terminating – sending distress	4.5.21	U		X	
41	Warnings – sending distress	4.5.22	U		X	
42	Tasks - receiving distress	4.5.23	U		X	
43	Display - receiving distress	4.5.24	U		X	
44	Handling received DSC messages – receiving distress	4.5.25	U		X	
45	Alarms – receiving distress	4.5.26	U		X	
46	Determining subsequent communication – receiving distress	4.5.27	U		X	
47	Automated tuning – receiving distress	4.5.28	U		X	
48	Acknowledgement – receiving distress	4.5.29	U		X	
49	Terminating – receiving distress	4.5.30	U		X	
50	Warnings – receiving distress	4.5.31	U		X	
51	Tasks – sending non distress	4.5.32	U		X	
52	Display - sending non distress	4.5.33	U		X	
53	Handling received DSC messages – sending non distress	4.5.34	U		X	
54	Alarms – sending non distress	4.5.35	U		X	
55	Automated tuning – sending non distress	4.5.36	U		X	
56	Delayed acknowledgement – sending non distress	4.5.37	U		X	
57	Terminating – sending non distress	4.5.38	U		X	
58	Warnings – sending non distress	4.5.39	U		X	
59	Tasks – receiving non distress	4.5.40	U		X	
60	Display - receiving non distress	4.5.41	U		X	

Harmonized Standard EN 301 025-3 The following requirements and test specifications are relevant to the presumption of conformity under article 3.3(e) of the R&TTE Directive [i.1]						
Requirement			Requirement Conditionality		Test Specification	
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No
61	Handling received DSC messages – receiving non distress	4.5.42	U		X	
62	Alarms – receiving non distress	4.5.43	U		X	
63	Automated tuning – receiving non distress	4.5.44	U		X	
64	Acknowledgement – receiving non distress	4.5.45	U		X	
65	Terminating – receiving non distress	4.5.46	U		X	
66	Warnings – receiving non distress	4.5.47	U		X	
67	Communication automated procedure	4.5.48	U		X	
68	Tasks – communication	4.5.49	U		X	
69	Display – communication	4.5.50	U		X	
70	Handling received DSC messages - communication	4.5.51	U		X	
71	Tuning of the receiver and transmitter - communication	4.5.52	U		X	
72	Termination – communication	4.5.53	U		X	
73	Handling incoming calls while engaged	4.5.54	U		X	
74	Termination of automated procedures	4.5.55	U		X	
75	Actions after termination of an automated procedure	4.5.56	U		X	
76	Putting automated procedures on hold	4.5.57	C	If the equipment is designed for handling procedures on hold	X	
77	Controlling non-terminated automatic procedures	4.5.58	C		X	

Key to columns:
Requirement:

No A unique identifier for one row of the table which may be used to identify an essential requirement or its test specification.

Description A textual reference to the requirement.

Clause Number Identification of clause(s) defining the essential requirement in the present document unless another document is referenced explicitly.

Requirement Conditionality:

U/C Indicates whether the requirement is to be *unconditionally* applicable (U) or is *conditional* upon the manufacturers claimed functionality of the equipment (C).

Condition Explains the conditions when the requirement shall or shall not be applicable for a technical requirement which is classified "conditional".

Test Specification:

E/O Indicates whether the test specification forms part of the *Essential Radio Test Suite* (E) or whether it is one of the Other Test Suite (O).

NOTE: All tests whether "E" or "O" are relevant to the requirements. Rows designated "E" collectively make up the Essential Radio Test Suite; those designated "O" make up the Other Test Suite; for those designated "X" there is no test specified corresponding to the requirement. The completion of all tests classified "E" as specified with satisfactory outcomes is a necessary condition for a presumption of conformity. Compliance with requirements associated with tests classified "O" or "X" is a necessary condition for presumption of conformity, although conformance with the requirement may be claimed by an equivalent test or by manufacturer's assertion supported by appropriate entries in the technical construction file.

Clause Number Identification of clause(s) defining the test specification in the present document unless another document is referenced explicitly. Where no test is specified (that is, where the previous field is "X") this field remains blank.

History

Document history		
V1.1.1	August 1998	Publication as EN 301 025
V1.1.1	May 2001	Publication
V1.2.1	September 2004	Publication
V1.3.1	February 2007	Publication
V1.4.1	September 2010	Publication
V1.5.0	May 2013	EN Approval Procedure AP 20130921: 2013-05-24 to 2013-09-23
V1.5.1	September 2013	Publication